

DP991T

Detector analógico óptico-térmico. Serie 990.

General

The DP991T is an elegant, slim-line, optical/heat multi-sensor with high performance analogue addressable features. Compensation for sensor drift is included as part of the internal signal-processing algorithm.

Operating Principles

The DP991T multisensor detector contains an optical smoke sensor and a temperature sensor whose outputs are combined to give the final decision of a possible fire situation. The way in which the signals from the two sensors are combined depends on the response mode selected. Five operating modes provide response behaviour which incorporates pure heat detection, pure smoke detection and a combination of both. The multisensor is therefore useful over the widest range of applications.

Unique Addressing

A unique, patented addressing method provides simple, user-friendly and accurate identification of monitor location whereby a coded card, inserted in the base, is read by any monitor as it is plugged in. All the electronic components are in the monitor, but the location information is held in the base. Addressing errors during maintenance and service are eliminated. Precoded and pre-numbered address cards are also available. These address cards simplify and speed up installation and commissioning.



Details

- 5 Approved response modes for ease of optimisation to different environments
- Rejection of transient signals
- Drift compensation to ensure constant sensitivity
- 360° Alarm visibility
- Flashing LED option
- Fast alarm reporting
- EN54 approved and CPR certified

DP991T

Detector analógico óptico-térmico. Serie 990.

Technical specifications

General

Indicación de estado 2 clear LEDs (red in alarm)

Eléctrico

Voltaje de funcionamiento 17 to 28 VDC

Voltaje de comunicación 5 - 9 V (peak to peak)

Consumo de corriente 400 μ A (quiescent)
3.5 mA (alarm)

Salida

Ratio y tipo de salida remote LED output 5 mA

Físico

Dimensiones físicas 50 x 100 (H x Ø)

Peso neto 105 g

Color Blanco

Material Policarbonato

Medioambiental

Temperatura de funcionamiento -20 to +60°C

Temperatura de almacenamiento -40 to +70°C

Humedad relativa 0 to 95% noncondensing

Environment Interior

Clasificación IP IP44

Regulatory

Certification EN54-5, EN54-7

Environmental

Max. wind (continuous) Not affected



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 January 2023 - 15:52