



DT2063N

Detector analógico térmico con salida de piloto remoto. Serie 2000.

General

The DT2063N is a 2000 series protocol, addressable heat detector certified to class A2R. It provides good looks as well as top features, including a rate-of-rise algorithm that allows the device to raise the alarm before the fixed temperature trigger point is reached. Dual fire LEDs indicate an alarm visible from all directions, eliminating the need for special detector orientation on installation, whilst a remote indicator output is provided as standard on every device.

Installation friendly

The DT2063N is individually identified by setting an address through two rotary switches. The address is a straight numerical value and does not require binary or hexadecimal conversions, significantly reducing the risk of incorrect addressing.

All 2000 series detectors are compatible with a standard base that makes them easily interchangeable.

State of the art communication

Panel to device communication is provided through a powerful SIA protocol featuring multiple bus cycle codes and CRC error checking and ensuring reliable communications between the device and the control panel.

This enhanced protocol ensures the overall integrity and error free operation of the full system, without compromising speed.

Extended applications

For varied applications the fixed temperature trigger level of the DT2063N may be set from the CIE to accommodate higher activation temperatures.

A comprehensive line of complimentary devices completes the 2000 series portfolio:

- common use detector bases
- optical, temperature and multi-sensors
- standalone and base isolators
- sounder circuit controllers
- conventional zone monitoring units
- various supervised and non-supervised I/O units
- a comprehensive line of manual call points
- loop powered notification devices and beam detectors



Details

- Dual thermistors
- Remote signaling capabilities
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range including optical and multi sensors
- Full range of I/O units and accessories
- Optional isolator base
- EN54:5 approved and CPR certified

DT2063N

Detector analógico térmico con salida de piloto remoto. Serie 2000.

Technical specifications

Geral

Indicación de estado	Dual red alarm LED
Interfaz de usuario	LEDs
Compatibilidad	Aritech 2000 series systems
Niveles de alarma	5
Conectividad	2000 Series bases

Elétrica

Voltaje de funcionamiento	17 to 28 VDC
Consumo de corriente	<270 μ A (quiescent at 24 VDC) 4.7 mA (alarm at 24 VDC)

Deteção

Principio de detección	Heat
Monitoring	Alarm threshold
Sensibilidad	Configurable
Área de cobertura	<80 m ²
Velocidad del aire	Unaffected
Temperatura de alarma	> +40°C
Rate-of-rise	Class A2

Saída

Cantidad de salidas	1
Ratio y tipo de salida	Remote indicator
Programable	No
Salida de alarma remota	4.7 mA

Físico

Dimensiones físicas	100 x 50 mm (Ø x H)
Peso neto	83 g
Color	Blanco nuboso (RAL 9001)
Tipo de Montaje	Montaje en el techo
Material	Plástico

Ambiental

Antivandálico	No
Temperatura de funcionamiento	-10 to +60°C
Temperatura de almacenamiento	-10 to +70°C
Temperatura ambiente	+25°C
Humedad relativa	10 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP20

Regulatory

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CPR
Normativas	EN54-5



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 10 February 2023 - 8:13