

AD105SS-0500

Cable sensor térmico digital 105°. Recubrimiento PVC y acero inoxidable. 500m.

General

The AD105SS-0100 is a Digital Linear Heat Detection (LHD) cable with a 105°C (221°F) fixed temperature activation rating. It has a Stainless Steel over PVC outer sheath offering increased mechanical protection and is supplied in 500m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' , 'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD105SS-0500

Cable sensor térmico digital 105°. Recubrimiento PVC y acero inoxidable. 500m.

Technical specifications

Eléctrico

Voltaje de funcionamiento 0 to 30VAC, 0 to 42VDC

Detección

Temperatura de alarma +105°C

Conductor

Resistencia 91 Ω /km (27.7 Ω /1000ft.)

Capacitancia < 73 pF/m (<22 pF/ft.)

Inductancia < 1.65 μ H/m (<0.5 μ H/ft.)

Físico

Peso neto 14.6 kg

Color Plata

Medioambiental

Humedad relativa 0 to 100% noncondensing

Entorno Interior, Exterior

Protección Cubierta de PVC, Trenzado de acero inoxidable

Regulatory

Certificación CE

Mechanical

Outside diameter (Nominal) 4.1mm \pm 0.12mm

No of cores 2

Colour Silver

Weight 14.6kg

Electrical

Operating voltage 0 to 30VAC, 0 to 42VDC

Environmental

Ambient temperature (max) 69°C (156°F)

Relative humidity 0% to 100%



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 24 August 2022 - 10:24