



EST-VES-8003-LNR

Integrated midi PA/VA unit: 8xAB (16 lines); amp 3x500W; 3xaudio; LCD, fireman mic.; charger; Rack-mounting version

Overview

EST-VES and EST-VES-8003 are scalable Public Address & Voice Alarm units suitable for multi-purpose architectures.

Devices from EST-VES and EST-VES-8003 series are voice alarm compact control units containing all components within one compact housing, which meet all the requirements of EN 54-16 and EN 54-4 (certificate of constancy of performance 1438-CPR-0659).

Whole concept of the system is based on the high quality audio network distribution nodes equipped either with two independent 160 W, 320 W or three independent transformerless 500 W class D amplifiers, which distribute 100 V signals to 4, 8 or 16 speaker lines depending on the type. The system also ensures operation of a backup amplifier for the Emergency priority type of signals.

All type of centrals are equipped with integrated backup power supply and EN 54-4 compliant charging unit.

EST-VES and EST-VES-8003 are designed to be a Plug & Play device with all elements expected from Voice Evacuation Systems; including a built-in fire microphone, touchscreen for global control, DSP, programmable contact inputs and buttons, time scheduler, charger with battery mounting space and expandable memory size for messages – all fitted into IP30 chassis or dedicated 15u rack for EST-VES-8003 8003LNR with 8003R.

EST-VES and EST-VES-8003 belongs to the family of independent EVAC systems which can be networked together and extended by desktop zone microphones or fireman microphones via TCP/IP network to provide live announcements and background music inputs. The system has been designed to be wired using CAT5 cables for paging microphones and fibre-optic redundant interlink connections between the systems.

All systems support up to 45 high quality audio signals distributed over 254 devices in the network.



Details

- Stand alone or TCP/IP network architecture
- All in one – independent rack mount EN 54-4 / 16 PA/VA unit
- Impedance speaker monitoring
- Remote management
- Up to 254 devices can be connected on the network (incl. fireman and zone microphones)
- Ability to connect standalone EST VES units via fiber optic / copper or both cables. Compatibility with RACK mounted modular EST ENT VES
- DSP audio processing on board
- Professional Sound Quality
- Evacuation, paging message and background music features
- Simple installation
- User friendly and intuitive programming software
- Rack-mounting version

EST-VES-8003-LNR

Integrated midi PA/VA unit: 8xAB (16 lines); amp 3x500W; 3xaudio; LCD, fireman mic.; charger; Rack-mounting version

Technical specifications

Entrada

Cantidad y tipo	1, Stereo to Mono
-----------------	-------------------

Salida

Cantidad y tipo	1, Mono
-----------------	---------

Físico

Dimensiones físicas	440 x 176 x 354 mm (W x H x D)
---------------------	--------------------------------

Color	Negro
-------	-------

Tipo de montaje	Montaje en bastidor
-----------------	---------------------

Medioambiental

Temperatura de funcionamiento	-5°C to +45°C
-------------------------------	---------------

Clasificación IP	30
------------------	----

Regulatory

Certificación	EN54-4
---------------	--------

Normativas	EN54-16
------------	---------

Environmental

Operating humidity	5 to 95% non-condensing
--------------------	-------------------------

Optional functions

Network card	2x SFP module 1 Gb/s, 1x POE 1 Gb/s, 100 Mb/s, 1x LAN 1 Gb/s, 100 Mb/s connection; RS485 port; 1xLAN/WAN 100 Mb/s connection
--------------	--

GUI	4,5" color touch screen
-----	-------------------------

DSP	Input EQ, outputs EQ, Feedback eliminator and audio limiter
-----	---

Standby battery

Battery working time	30 hours + 30 minutes evacuation
----------------------	----------------------------------

Physical

Gross weight	16.6 kg
--------------	---------

No of messages played at the same time	3
--	---

Protection	Over-temperature, short circuit, overload, ground leakage
------------	---

No of AB zones	8
----------------	---

No of speaker lines	16
---------------------	----

No of control inputs	7
----------------------	---

No of relay outputs	3
---------------------	---

No of amplifiers / Power	3 / 500 W RMS
--------------------------	---------------



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 April 2023 - 18:41