

# ZR485-3

## Radio Call Point, complete with battery pack (red)

### General

---

The ZR485-3 is a wireless, indoor, manual call point operating on 868 MHz.

### Wireless systems

---

The ZR485-3 provides a manual means of initiating a fire alarm in areas where the installation of hard wiring is not an option. The unit is controlled from the main fire alarm panel via a loop wired radio interface module. This arrangement allows both wireless and hardwired devices to be seamlessly located on the same loop wiring.

The ZR485-3 forms part of an extensive range of wireless fire alarm devices that includes both smoke/heat detection as well as notification devices, sounder/beacons and IO units.

Suitable for use on installations specifying the recommendations of BS 5839 Part 1, the callpoint fully meets the requirements of European Standard EN54 Part 11 and is CPD certified.

### System operation

---

The ZR485-3 is operated either by pressing a resettable element (optional) or by breaking a frangible glass with finger pressure. The glass element has a clear vinyl coating on the front surface to prevent operator injury and to inhibit the release of loose fragments as the glass is broken. Both operating elements are easily interchangeable.

Every wireless device controlled through the RLM interface is assigned its own IDENT address with which the main control panel communicates with it. This provides the same system functionality to wireless as well as traditionally hard-wired devices.

### System testing

---

The ZR485-3 is designed for surface mounting and is supplied complete with matching back box. System testing is carried out by using a special key supplied with the call point. When inserted into a slot in the base of the call point moulding, the device is triggered to operate automatically.

Rated at IP42 the ZR485-3 is constructed of ABS plastic and is intended for indoor applications. A red LED indicator, prominently positioned on the call point front plate, flashes when the unit is operated.



### Details

---

- Fully addressable
- Full wireless device status monitoring
- 2-way radio communication
- 5 year battery life at normal conditions
- Dual battery supply
- Range in excess of 150 metres
- No external aerials
- System test facility via test key
- CPD certified

# ZR485-3

## Radio Call Point, complete with battery pack (red)

### Technical specifications

---

#### General

---

Wireless frequency 868 MHz

---

#### Electrical

---

Power supply type Batteries

---

Operating voltage 3.2 VDC  
6 x AA cell Duracell alkaline batteries

---

Output transmitter power 0-14dBm (Variable)

---

#### Physical

---

Physical dimensions 87 x 87 x 61.5 mm

---

Net weight 276 g

---

Colour Red

---

Mounting type Surface mount

---

Material (body) Moulded ABS

---

#### Environmental

---

Operating temperature -10 to +70°C

---

Relative humidity 10 to 95% noncondensing

---

Environment Indoor

---

IP rating IP24

---

#### Regulatory

---

Certification EN54-11, EN54-25

---

Approval EN54:11/25, ENTSI 300:220

---

#### Description

---

Wireless manual callpoint

---

#### Compatibility

---

All ZP addressable systems via RLM

---

#### Monitoring

---

Continuously self-checking

---

#### Indication

---

Alarm LED (red)

---

#### Compatible products

---

Category	Reference	Description
Detection device	DM715	EN54 Universal MCP glass, without branding
Detection device	DMN782	Hinged transparent MCP protection cover
Detection device	DMN800	Resettable element for Manual Call Point

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 4 September 2023 - 10:32