

ZP785KS-N

ZP785 addressable Manual Call Point (MCP), red, 2 positions. keyswitch, surface mount

General

The ZP785KS-N is a RED, high quality addressable key switch call point providing a manual means of initiating a fire alarm on ZP addressable fire systems. The key allows for on/off control of equipment such as ventilation systems and overrides, and prevents unauthorised access to the system.

The key switch has 2 positions, with the key being trapped in one position and removable in the other. Changing between these positions require the turn of the key through a 90° angle. It offers three electrical connections which already come fitted with fly-leads. One of these connections are common while the tuning of the key result in the changeover between the other two.

Loop Connection

Installed as part of ZP addressable fire alarm systems, up to 127 devices consisting of detectors, call points and/or interface units may be connected to each of the control panel loops. All loop devices incorporate switch settings enabling them to be assigned a unique address which is polled by the panel every two seconds.

ZP785-3 call points are designed for semi recessed fixing or surface mounting. The ZP785KS-N is supplied with all required back boxes to allow for surface mounting, and is supplied with 2 sturdy keys.

Construction

Rated at IP21 the ZP785KS-N is constructed of ABS plastic and intended for indoor applications. The robust switching device comprises a main housing and escCarrierheon plate. It is fitted to the plate which simply snaps into the main housing and is permanently located in place with fixing screws.



Details

- Modern stylish design
- Easy to install
- High quality key switch
- Preformed mounting slots
- EN54 'burning house' functional marking
- Surface mount

ZP785KS-N

ZP785 addressable Manual Call Point (MCP), red, 2 positions. keyswitch, surface mount

Technical specifications

Electrical

Operating voltage Loop 19.5 to 20.5 V

Physical

Physical dimensions 87 x 87 x 62mm (H X W X D)

Net weight 184 g

Colour Red

Mounting type Back box

Material (body) Moulded ABS

Material Moulded ABS

Colour Red

Weight 184g

Dimensions (h x w x d) 87 x 87 x 62mm

Environmental

Operating temperature -20 to +55°C

Storage temperature -20 to +70°C

Relative humidity 0 to 95% noncondensing

Environment Indoor

IP rating IP21

Application Indoor installation

IP rating IP21

Operating temperature -20°C to +55°C

Storage temperature -20°C to +70°C

RH range 0 to 95%
(noncondensing)

Compatibility

All ZP7 addressable systems

Operating voltage

19.5 to 20.5 V

Current

Quiescent 400µA

Alarm 450µA

Addressing method

7 way dipswitch

Mounting

Surface

Wiring

2 core loop

Monitoring

Open/short circuit, removal & device type

Operating principle

Keyswitch

Indication

Alarm LED (red)

EMC

CE marked (EEC89/336)



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 September 2023 - 11:38