

# GST301

## Conventional Extinguishing Control Panel

### General

The GST301 is a stand-alone CIE (Control and Indicating Equipment) intended for use as a single area extinguishing system controller. The function of the panel is to monitor 2 extinguishing zones for alarm condition and provide the appropriate audible/visible indication and controls. Initiating of extinguishing agents are possible both manually or automatically.

### Installation

The GST301 CIE is designed for wall mounting. It's compact design includes a power supply and battery charger, with room for standby batteries inside the panel housing.



### Details

- 3 Detection zones, 2 for extinguishing and 1 for standard zone protection
- 2 Extinguishing zones for double knock (coincidence) detection
- Automatic and manual extinguishing control possible
- Numerical 7-segment countdown timer indication
- Configurable discharge release delay time
- Fully supervised extinguishing circuits
- Two phase evacuation sounders
- Day/Night mode selectable
- Configurable extinguishing output
- Built-in power supply and battery charger
- Space for batteries inside the panel cabinet

# GST301

## Conventional Extinguishing Control Panel

### Technical specifications

#### General

|  |  |
|--|--|
| Status indicator                       | 7-Segment display and LEDs                 |
| Compatibility                          | GST DC-9000E series conventional detectors |
| Maximum system capacity (device count) | up to 96                                   |

#### Electrical

|                     |                   |
|---------------------|-------------------|
| Power supply type   | 220/230 VAC       |
| Power consumption   | ≤20 W (Quiescent) |
| Operating voltage   | 27 VAC            |
| Current consumption | < 1 A             |
| Mains frequency     | 50/60 Hz          |

#### Zone

|                              |                                  |
|------------------------------|----------------------------------|
| Maximum zone capacity        | up to 3                          |
| Operating voltage            | 24 VDC                           |
| Quantity of devices per zone | 15 detectors / 32 MCPs           |
| Cable rating                 | 1.5 mm <sup>2</sup> (1000 m max) |

#### Input

|                       |   |
|-----------------------|---|
| Input quantity        | 2                                       |
| Input type and rating | Extinguishing override, Pressure switch |
| Termination           | Input specific                          |

#### Output

|                       |                            |
|-----------------------|----------------------------|
| Output quantity       | 6                          |
| Fire alarm signalling | 1, NO/NC                   |
| Fault signalling      | 1, NO/NC                   |
| Notification          | 2, 300 mA @ 24 VDC         |
| Auxilliary power      | < 100 mA @ 24 VDC          |
| Programmable          | Yes                        |
| Termination           | 4.7 kΩ                     |
| Agent release         | 1, <2 A @ 24, Single pulse |

#### Standby battery

|                                |            |
|--------------------------------|------------|
| Capacity                       | 7 Ah       |
| Charging                       | 300 mA     |
| Batteries supported in housing | 2 x 12 VDC |

#### Physical

|                     |                                |
|---------------------|--------------------------------|
| Form factor         | Small                          |
| Physical dimensions | 300 x 350 x 110 mm (W x H x D) |
| Colour              | Beige                          |
| Mounting type       | Surface mount, Wall mount      |
| Cable entries       | 5                              |
| Material            | Metal                          |

#### Environmental

|                       |                        |
|-----------------------|------------------------|
| Vandal proof          | No                     |
| Operating temperature | 0 to 40°C              |
| Relative humidity     | 0 to 95% noncondensing |
| Environment           | Indoor                 |

#### Compatible products

| Category         | Reference | Description                           |
|------------------|-----------|---------------------------------------|
| Detection device | C-9317    | Extinguishing Override Control device |



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [za.firesecurityproducts.com](http://za.firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2023 - 10:33