

IO956I

Módulo analógico de 1 salida de sirena con aislador. Serie 950.

General

The IO956I is an addressable sounder controller. It is designed to control sounders powered by an external DC supply. Sounders are switched continuously or pulsed, and may be synchronised.

Interfaces for intelligent systems

The IO956I is designed to suit individual applications. This standard interface is designed to be surface mounted to walls and consist of three parts: a back box with knockouts for cable entry, a PCB assembly and a protective front cover.

Interface with isolator

The IO956I is fitted with a bi-directional short-circuit isolator so that they are unaffected by a single short-circuit on either loop input or output.

Sounder Control

The IO956 is normally used to control a zone of sounders powered by an external DC supply. The sounders will be switched to sound continuously or be pulsed, 1s on, 1s off.

An opto-coupled input is provided to monitor the state of the external power supply.



Detalles

- LEDs for signalling of I/O and fault condition
- Aesthetically pleasing
- On board loop isolators
- Easy to install
- Well protected
- Modular design

|0956|

Módulo analógico de 1 salida de sirena con aislador. Serie 950.

Especificaciones técnicas

Eléctrico

Voltaje de funcionamiento 17 to 28 VDC

Consumo de corriente 1.9 mA

Físico

Color Blanco

Medioambiental

Temperatura de funcionamiento -20 to +70°C

Humedad relativa 0 to 95% noncondensing

Entorno Interior

Clasificación IP IP54

Regulador

Certificación EN54-17, EN54-18

Supply voltage

17 - 28 VDC

Current consumption (Loop current)

Switch on surge (100 ms) 2.6 mA

Quiescent (with 10kOhm) 1.9 mA

Output active 1.7 mA

Fault 3.5 mA

Short circuit 4.5 mA

Current consumption (External supply)

Relay off 1 mA @ 9 VDC or 3 mA @ 32 VDC

Sounders ON (excluding sounder load) 44 mA @ 9 VDC or 47 mA @ 32 VDC

Sounder Voltage (max)

50 VDC

Sounder Current (max)

1 A @ 30 VDC

Supervision

9 - 11 VDC

Operating temperature

-20°C to +70°C

Relative humidity (non condensing)

0-95%

Ingress protection

IP54



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 14 February 2024 - 16:38