

FC-200-003

Fusion wireless manual call point with flip cover (Red)

General

The FC-200-003 is an RED addressable, wireless, resettable manual call point including batteries. It is suitable for indoor use and connects to a Fusion or Ziton gateway.

Batteries typically have a minimum of three-year life expectancy.

Overview

The FC-200-003 call point is quick and easy to install and offers individual addressing at the fire control panel. Dual band 868 MHz operation, auto adjusting power output, fire indication LED, resettable element, anti tamper and a test key are standard features. A transparent hinged cover is also included for protection against accidental operation in busy environments.

This device is third party EN certified and compatible with the EMS FireCell system, EMS Fusion Radio Loop Module (RLM), EMS Wireless Zone Monitor (WZM) as well as Ziton ZPR868 series wireless interfaces.

Operating Principle

Fire detection is often required in buildings where cabling presents a challenge because of the design or architecture of the building. Wireless installation provides the ideal solution to these environments.

Ideal for the application in hybrid systems where both wired and wireless devices share the same CIE, up to five gateways may be installed on any wired CIE loop. Up to five gateways can easily be incorporated on a single installation (with larger systems possible through design), using an easy to use, site survey kit to confirm the positioning of the wireless devices. Every gateway supports up to 31 wireless devices.

Every wireless device is assigned an address which is recognised by the control panel in the same way as is the address of any wired device connected directly to the CIE loop wiring.



Details

- Dual band 868 MHz operation
- Fire indication LED
- Resettable element
- Anti tamper locking
- Protective cover
- Third party EN certified

FC-200-003

Fusion wireless manual call point with flip cover (Red)

Especificaciones técnicas

General

Indicación de estado	LED
Frecuencia inalámbrica	868 MHz
Compatibility	Fusion gateway FCX-532-001, Ziton gateways ZPR868 series
Conectividad	Wireless
Método de direccionamiento	Electronic

Eléctrico

Tipo de fuente de alimentación	Baterías
Baterías	6x AA Alkaline (Panasonic LR6AD Powerline / Varta 4006 Industrial)
Voltaje de funcionamiento	2.8 to 5 VDC
Potencia del transmisor de salida	0 to 25 mW, 0 to 14 dBm (auto adjusting)

Detección

Principio de detección	Microswitch
Supervisión	Device type, Presence, Tamper
Área de cobertura	Dependant on local regulations
Installation height	Determined by local regulation

Físico

Dimensiones físicas	90 x 98 x 72.5 mm (W x H x D)
Peso neto	350 g
Color	Rojo
Tipo de Montaje	Montaje en pared
Entradas de cable	NA
Material (caja)	ABS
Marcado funcional	House on fire

Medioambiental

Vandal proof	No
Temperatura de funcionamiento	-10 to 55°C
Temperatura de almacenamiento	+5 to +30°C
Humedad relativa	0 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP24

Regulador

Cumplimiento	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certificación	CPR
Normativas	EN54-11, EN54-25



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 10:40